














iT-K BT WIFI

MOBILE VERSION

-  DATA TRANSMISSION
-  CANCELLATION RECEIPT
-  RETURN RECEIPT
-  RECEIPT WITH ID CODE
-  VAT RATES PROGRAMMING
-  QR CODE PRINT (FROM PC)
-  CLOUD SERVICES
-  REMOTE MONITORING **DWS**
-  WIFI CONNECTION (SMARTPHONE HOTSPOT)

-  PVC COVER AND SILICON MEMBRANE FOR KEYBOARD
-  BAG IN WATER-REPELLENT MATERIAL WITH INTERNAL POCKETS FOR DOCUMENTS (OPTIONAL)



Scales



Scanner



External display



EFC POS



Drawer



PC

MAIN CONNECTIONS



CERTIFIED FOR THE MOST HOSTILE ENVIRONMENTS AND WORKING CONDITIONS

MOBILE VERSION

TECHNICAL DETAILS

KEYBOARD: Compact, 38 programmable keys

PRINTER: thermal printer, 8dot/mm, 58mm, easy loading, automatic aper cutter, 90m roll length - 75 mm/sec printer speed

DGFE/DETAIL MEMORY: MMC certified RT

OPERATOR DISPLAY: backlit LCD, 2 lines x 16 alphanumeric characters

CUSTOMER DISPLAY: backlit LCD, 2 lines x 16 alphanumeric characters

DEPARTMENTS: 6 direct, 4 programmable

PLU: 50 programmable (up to 7000 with optional memory expansion)

GROUPS: 5 programmable

OPERATORS: 8

FOREIGN CURRENCY: 4 programmable

VAT RATE: 8 programmable + 6 no-taxable status + 1 ventilation

ACCOUNTING FUNCTIONS: Withdraw, deposit, paid-out, receipt on account

RECEIPT CLOSING: 10 tenders , 20 programmable sub-tenders

GENERAL FUNCTIONS: %discount, value discount, refund, correction of previous transaction, avoid of current receipt, programmable price, price variation, macro from keyboard, automatic change due, real clock, banknote checker, cloud services

GRAPHICS: Customizable advanced graphics on receipt via PC: logo, lottery, promotions, jolly

DRAWER: 6VDC

DRIVER CONNECTION: driver for Windows XP/Vista/7/8/10 Linux - driver standard: POS for .net (UPOS), OlePOS Protocolli: Xon/Xoff

CONNECTIONS: PC to issue receipts, Barcode, Electronic scales, Drawer, EFT POS, POS printer, External display

CONNECTIONS: COM 1: 1 mini USB (PC) COM 2: 1 standard RS232 (scale, barcode scanner)

POWER SUPPLY: 9 V DC with LAN adapter 220V

DIMENSIONS: 190 x 354 x 100 mm (D x W x H)

WIFI



+ OPTIONAL BAG



+ KEYBOARD SILICON PROTECTION

KEYBOARD SILICON PROTECTION

PURE WHITE



Ditron S.R.L.

Via Antiniana, 115 - 80078 Pozzuoli (NA) - Italy

e-mail: commercial@ditron.eu - phone: +39 0812428557

sito: www.ditron.eu